## Advantage® Surface Activator

- Product Information





# What is Advantage® Surface Activator?

Alltimes Advantage® Surface Activator is formulated specifically for use with Advantage® for Gutters. This specially formulated cleaner is a high performance solution that prepares the surface and removes any contaminants prior to applying further coats of Advantage® for Gutters once the 9 hour overcoat-ability window has closed.



## Why choose Advantage® Surface Activator

- ✓ Powerful and effective cleaner
- ✓ Low odour
- Allows surface to be over coated
- ✓ Biodegradable

#### **General Information**

Feature:	Result:
Shelf Life:	24 months minimum in unopened tins, stored in a cool dry place out of direct sunlight
Form:	Liquid
Colour:	Colourless
Odour:	Characteristic
Specific Gravity	0.951 @25°C
Temp. Limits:	5°C - 30°C

### Advantage® Surface Activator

- Application Guide



#### **Surface Preparation**

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory.



#### **Application**

- Spray on Advantage® Surface Activator, ensuring the surface is saturated, allow to work for 30 seconds.
- Agitate the surface with a scotch pad making sure it does not dry out.
- Wipe the surface clean with an absorbent, lint free cloth, ensuring the cloth is changed every 1m<sup>2</sup>.
- Ensure the surface is completely matt with no visible shine.
- Allow the surface to completely dry before applying Advantage® for Gutters.

#### Precautions for Use

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

### Cleaning of Equipment

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.



Alltimes Coatings, Units C & D, Station Road Industrial Estate, South Woodchester, Stroud, Gloucestershire. GL5 5EQ. UK

T: 01453 872 850

E: info@alltimescoatings.co.uk W: www.alltimescoatings.co.uk

No responsibility can be taken by the manufacturers where conditions of use are beyond our control. All products should be used in accordance with the manufacturer's instructions. For further information please refer to the application guide and Material Safety Data Sheet. This information and guidance is given in good faith and without prejudice and liability, Technical and Safety Data must be observed. All coverages are given as a guide only, as volumes will vary with profile, porosity and method of application. Loss factors should also be taken into account.

6