

Advantage<sup>®</sup> for Gutters Safety Data Sheet



## Advantage<sup>®</sup> for Gutters



Moisture tolerant gutter coating system applied in a single coat. Solvent free hybrid coating with excellent UV, mechanical and temperature resistance.

#### AG SDS 4/24

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product Identifier

Product Name:	Advantage <sup>®</sup> for Gutters
Product Number:	ATAVGDG

#### 1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Identified Users:	Coating for Roof Maintenance & Repair
luentineu Osers.	

#### 1.3 Details of the Supplier of the Safety Data Sheet

Supplier:	Alltimes Coatings Limited, Units C & D, Station Road Industrial Estate,
Supplier.	South Woodchester, Stroud, Gloucestershire. GL5 5EQ. UK

#### 1.4 Emergency Contact Numbers

Telephone:	01455 272 278
Mobile:	07773 329 424

#### **SECTION 2: Hazards Identification**

## 2.1 Classification of the Substance or Mixture Classification (EC 1272/2008)

Physical Hazards:	Not Classified
Health Hazards:	Skin Sens. 1 - H317
Environmental Hazards:	Aquatic Chronic 3 - H412

#### 2.2 Label Elements

Pictogram:	
Signal Word:	
Hazard Statements:	H412 Harmful to aquatic life with long lasting effects.
Precautionary Statements:	P102 - Keep out of reach of children. P261 - Avoid breathing vapour/spray. P262 - Do not get in eyes, on skin or clothing. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301+P330+P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. P33+P313 If skin irritation or rash occurs:Ge medical advice/attention. P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P314 - Get medical advice/attention if you feel unwell. P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P235 - Store in a well ventilated place. Keep cool. P501 -Dispose of contents and container to an approved waste disposal point
Contains:	Reaction mass of Pentamethyl-Piperidyl Sebacate

#### 2.3 Other Hazards

Other Hazards:	-
----------------	---

#### **SECTION 3: Composition/Information on Ingredients**

#### 3.1 Mixtures

Titanium Dioxide:	1 - 5%
CAS Number:	13463-67-7
EC Number:	236-675-5
REACH Registration Number:	012119489379-17-XXXX
Classification:	Not Classified
Reaction Mass of Pentamethyl-Piperidyl Sebacate:	1%
CAS Number:	
REACH Registration Number:	012119491304-40-XXXX

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

1

1

M Factor (Acute):

M Factor (Chronic):

## 4.1 Description of First Aid Measures

General:	If in doubt, get medical attention promptly. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Inhalation:	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air at once. Get medical attention.
Ingestion:	Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention.
Skin Contact:	Wash skin thoroughly with soap and water.
Eye Contact:	Wash affected eyes for at least 15 minutes under running water with eyelids held open.
Protection of First Aiders:	No action shall be taken without appropriate training or involving any personal risk. First aid personnel should wear appropriate protective equipment during any rescue. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves.

#### 4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Inhalation:	No significant hazard at normal ambient temperatures.
Ingestion:	No specific symptoms known.
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.
Eye Contact:	No specific symptoms known.

#### 4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

Notes of the Doctor:	Treat symptomatically.
Specific Treatments:	No specific chemical antidote is known to be required after exposure to this product.

#### **SECTION 5: Firefighting Measures**

#### 5.1 Extinguishing Media

Suitable Extinguishing Media:	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable Extinguishing Media:	Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2 Special Hazards Arising from the Substance or Mixture

Specific Hazards:	Containers can burst violently or explode when heated, due to excessive pressure build-up. Harmful to aquatic life with long lasting effects.
Hazardous Combustion Products:	<b>Thermal decomposition or combustion products may include the following</b> <b>substances:</b> Carbon dioxide (CO2), Carbon monoxide (CO), Acrid smoke or fumes. Oxides of nitrogen, Halogenated hydrocarbons, Metal oxide(s).

## 5.3 Advice for Firefighters

	In case of fire: Evacuate area. No action shall be taken without appropriate
Protective Actions During Firefighting:	training or involving any personal risk. Cool containers exposed to heat with water
	spray and remove them from the fire area if it can be done without risk. Control
	run-off water by containing and keeping it out of sewers and watercourses.
	Wear positive-pressure self-contained breathing apparatus (SCBA) and
Special Protective Equipment for	appropriate protective clothing. Firefighter's clothing conforming to European
Firefighters:	standard EN469 (including helmets, protective boots and gloves) will provide a
	basic level of protection for chemical incidents.

## 6.1 Personal Precautions, Protective Equipment and Emergency Procedures

	No action shall be taken without appropriate training or involving any personal
	risk. Evacuate area. Keep unnecessary and unprotected personnel away from
For Non-Emergency Personnel:	the spillage. Do not touch or walk into spilled material. Do not breathe gas, fume,
For Non-Emergency Personnel.	vapours or spray. Provide adequate ventilation. If ventilation is inadequate,
	suitable respiratory protection must be worn. Use protective equipment
	appropriate for surrounding materials.
For Emergency Personnel:	Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2 Environmental Precautions

	Avoid the spillage or runoff entering drains, sewers or watercourses. Inform the
Environmental Precautions:	relevant authorities if environmental pollution occurs (sewers, waterways, soil or
	air). Contain spillage with sand, earth or other suitable non-combustible material.

#### 6.3 Methods & Material for Containment and Cleaning

	<b>Small Spillages:</b> Stop leak if safe to do so. Move containers from spillage area. Absorb spillage with non-combustible, absorbent material. Place waste in labelled, sealed containers.
Methods for Cleaning Up:	<b>Large Spillages:</b> Stop leak if safe to do so. Move containers from spillage area. Approach the spillage from upwind. No smoking, sparks, flames or other sources of ignition near spillage. Avoid the spillage or runoff entering drains, sewers or watercourses. Dispose of waste via a licensed waste disposal contractor. The contaminated absorbent may pose the same hazard as the spilled material.

## 6.4 Reference to Other Sections

Reference to Other Sections:	For personal protection, see Section 8. For waste disposal, see Section 13.
------------------------------	-----------------------------------------------------------------------------

#### **SECTION 7: Handling and Storage**

#### 7.1 Precautions for Safe Handling

Note: The information in this section contains generic advice and guidance.
-----------------------------------------------------------------------------

	Contains epoxy constituents. May produce an allergic reaction. Use only in well-
	ventilated areas. Wear protective clothing as described in Section 8 of this safety
Usage Precautions:	data sheet. Inhalation of dust during cutting, grinding or sanding operations
	involving this product may cause irritation of the respiratory tract. Avoid contact
	with skin and eyes.
	In confined or poorly-ventilated spaces, a supplied-air respirator must be worn.
	Do not eat, drink or smoke when using this product. Good personal hygiene
Advice on General	procedures should be implemented. Wash hands thoroughly after handling.
Occupational Hygiene:	Take off contaminated clothing and wash it before reuse. Remove contaminated
	clothing and protective equipment before entering eating areas. Change work
	clothing daily before leaving workplace.

## 7.2 Conditions for Safe Storage, Including Any Incompatibilities

alkalis. Read label before use. Avoid exposure to high temperatures or direct	Storage Precautions:	Store in accordance with local regulations. Store in tightly-closed, original container. Avoid contact with oxidising agents. Avoid contact with acids and
		alkalis. Read label before use. Avoid exposure to high temperatures or direct sunlight. Keep container tightly sealed when not in use.

## 7.3 Specific End Use(s)

Specific End Use(s): The identified u

The identified uses for this product are detailed in Section 1.2.

#### SECTION 8: Exposure Controls/Personal Protection

## 8.1 Control Parameters Occupational Exposure Limits

Titanium Dioxide	
Long-Term Exposure Limit (8 Hour TWA):	WEL 10 mg/m³ inhalable dust
Long-Term Exposure Limit (8 Hour TWA):	WEL 4 mg/m³ respirable dust

Titanium Dioxide	
DNEL	Workers - Inhalation; Long term local effecs: 10mg/m3
PNEC	Intermittent release: 0.61 mg/l, Fresh Water: 0.127 mg/l, Marine water: 1mg/l, Sediment (Freshwater): 1000mg/kg, Sediment (Marinewater): 100mg/kg, Soil: 100mg/kg, STP: 100mg/l
Pentamethyl-Piperidyl Substrate	
DNEL	Workers - dermal: short term systemic effects: 2.5mg/kg, Workers - Inhalation: Short term systemic effects: 2.35mg/m3, Workers - Inhalation; Long term systemic effects: 2.35 mg/m3, Workers - Dermal; Long term systemic effects: 2.5mg/kg
PNEC	Intermittent release: 0.009mg/l, Fresh water: 0.0022mg/l, Marine water: 0.0022mg/l, Sediment (Freshwater): 1.05mg/kg, Sediment (Marinewater): 0.11mg/ kg, Soil: 0.21mg/kg, STP: 1mg/l

## 8.2 Exposure Controls

Appropriate Engineering Controls:	As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion- proof ventilating equipment.
Eye/Face Protection:	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Chemical splash goggles or face shield.
Hand Protection:	<ul> <li>To protect hands from chemicals, gloves should comply with European</li> <li>Standard EN374. The most suitable glove should be chosen in consultation</li> <li>with the glove supplier/manufacturer, who can provide information about the</li> <li>breakthrough time of the glove material. Considering the data specified by</li> <li>the glove manufacturer, check during use that the gloves are retaining their</li> <li>protective properties and change them as soon as any deterioration is detected.</li> <li>It is recommended that gloves are made of the following material: Butyl rubber.</li> <li>Nitrile rubber.</li> </ul>
Other Skin & Body Protection:	<ul> <li>Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. For the greatest protection, clothing should include anti-static overalls, boots and gloves.</li> <li>Refer to European Standard EN 1149 for information on material and design requirements and test methods.</li> </ul>
Hygiene Measures:	Good personal hygiene procedures should be implemented. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Remove contaminated clothing and protective equipment before entering eating areas. When using do not eat, drink or smoke. Eye wash facilities and emergency shower must be available when handling this product.
Respiratory Protection:	If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. When spraying, wear a suitable supplied-air respirator.
Environmental Exposure:	Emissions from ventilation or work process equipment should be checked to ensure they controls comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

#### **SECTION 9: Physical and Chemical Properties**

## 9.1 Information on Basic Physical and Chemical Properties

Appearance:	Liquid
Colour:	Off-white
Odour:	Pleasant, agreeable
Flash Point:	Above 60°C
Vapour Density:	Heavier than air
Relative Density:	~ 1.40 @ 20°C
Solubility(ies):	Immiscible with water
Viscosity:	Kinematic viscosity > 20.5 mm²/s

## 9.2 Other Information

#### Volatile Organic Compound:

This product contains a maximum VOC content of 1 g/l.

SECTION 10: Stability and Reactivity		
10.1 Reactivity		
Reactivity:	No test data specifically related to reactivity available for this product or its ingredients.	
10.2 Chemical Stability		
Stability:	Stable at normal ambient temperatures and when used as recommended.	
10.3 Possibility of Hazardous Reactions		
Possibility of Hazardous Reactions:	Under normal conditions of storage and use, no hazardous reactions will occur.	
10.4 Conditions to Avoid		
Conditions to Avoid:	Avoid heat, flames and other sources of ignition. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition. Avoid the accumulation of vapours in low or confined areas.	
10.5 Incompatible Materials		
Materials to Avoid:	Avoid contact with the following materials: Oxidising agents.	
10.6 Hazardous Decomposition Products		
Hazardous Decomposition Products:	Does not decompose when used and stored as recommended.	
SECTION 11: Toxicological Information		
11.1 Information on Toxicological Effects Acute Toxicity - Inhalation		
ATE Inhalation (vapours mg/l):	883.75	
SECTION 12: Ecological Information		
12.1 Toxicity 12.2 Persistence and Degradability 12.3 Bioaccumulative Potential		

12.4 Mobility in Soil 12.5 Results of PBT and vPvB Assessment 12.6 Other Adverse Effects

Reactivity: No test da ingredient	ta specifically related to reactivity available for this product or its s.
-----------------------------------	-------------------------------------------------------------------------------

#### 13.1 Waste Treatment Methods

General Information:	The generation of waste should be minimised or avoided wherever possible.
	Disposal of this product, process solutions, residues and by-products should at
	all times comply with the requirements of environmental protection and waste
	disposal legislation and any local authority requirements.
Disposal Methods:	Do not empty into drains. Waste packaging should be collected for reuse or
	recycling. Incineration or landfill should only be considered when recycling is not
	feasible.
Waste Class:	08 01 11 Waste paint and varnish containing organic solvents or other dangerous
	substances If this product is mixed with other wastes, this code may no longer
	apply. If mixed with other wastes, the appropriate code should be assigned. For
	further information, contact your local waste authority.
General:	The product is not covered by international regulations on the transport of
	dangerous goods (IMDG, IATA, ADR/RID).

## **SECTION 14: Transport Information** 14.1 UN Number UN Number: Not applicable. 14.2 UN Proper Shipping Name UN Shipping Name: Not applicable. 14.3 Transport Hazard Class(es) Transport Hazard Class(es): No transport warning sign required. 14.4 Packaging Group Packaging Group: Not applicable. 14.5 Environmental Hazards Environmental Hazards: Environmentally hazardous substance/marine pollutant? - No. 14.6 Special Precautions for User **Special Precautions for User:** Not applicable.

#### 14.7 Transport in Bulk According to Annex II of MARPOL and the IBC Code

<b>Transport in Bulk According to</b> Annex II of MARPOL 73/78 and the IBC Code:	Not applicable.
of MARPOL 73/78 and the IBC Code:	

# 15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

EU Legislation:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Health & Environmental Listings:	None of the ingredients are listed.
Authorisations (Title VII Regulation 1907/2006):	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006):	No specific restrictions are known for this product.

#### 15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out.

#### **SECTION 16: Other Information**

Revision Date:	16/05/2022
Revision:	4
Abbreviations & Acronyms Used in the Safety Data Sheet:	ATE = Acute Toxicity Estimate
	CLP = Classification, Labelling & Packaging Regulation
	DNEL = Derived No Effect Level
	EUH Statement = CLP - Specific Hazard statement
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	WEL = Workplace Exposure Limit
	H412 Harmful to aquatic life with long lasting effects.
Hazard Statements in Full:	
Shelf Life:	1 Year

No responsibility can be taken by the manufacturers where conditions of use are beyond our control. All products should be used in accordance with the manufacturer's instructions. For further information please refer to the application guide and Material Safety Data Sheet. This information and guidance is given in good faith and without prejudice and liability, Technical and Safety Data must be observed. All coverages are given as a guide only, as volumes will vary with profile, porosity and method of application. Loss factors should also be taken into account.



Alltimes Coatings, Units C & D, Station Road Industrial Estate, South Woodchester, Stroud, Gloucestershire. GL5 5EQ. UK

T: 01453 872 850

E: info@alltimescoatings.co.uk

W: www.alltimescoatings.co.uk