



Advantage® Metal Primer with Graphene



Unique Graphene enhanced Anti Corrosion primer to coat and protect prepared steel before application of Advantage® Top Coats.

Benefits

- ✓ Damp tolerant during application
- ✓ Graphene enhanced
- ✓ Protects corroded steel surfaces
- ✓ Used to protect steel surfaces in aggressive weather environments
- ✓ Low film weight
- ✓ Single pack
- ✓ Good re-coat times
- ✓ UK underwritten

✓ **Long Product Warranty -**
30 years for metal roofs,
20 years for asbestos cement
roofs, 15 years for gutters
and cut edge corrosion

● **Full UK underwritten**
Insurance
Subject to Contractor Status

✓ **Free training and CPDs**
available on request



Advantage® Metal Primer with Graphene Product Data Sheet

Preparation and Cleaning

Power-wash using 3,000 psi. water pressure minimum or clean surface thoroughly to ST2 standard, you will find this more effective with a rotary cleaning head. All oil, grease and dirt must be removed prior to application.

New galvanising should be clean. Weathered galvanising should have white zinc salts removed.

Tighten all fixings if possible and crop them so they're as short as possible.

Application

Apply one coat of Advantage® for Metal Primer with Graphene by brush or roller to all affected areas allow at least 3 hours to cure.

Primer should be completely dry before applying the top coat.

Brush or roller application is advised on damp surfaces.

Apply with a full brush, avoid excessive brushing out.



Contact our technical department for advise on spray application.

Technical Data

Coverage:	Theoretical 4-5m ² per 1L <small>(depending on substrate)</small>
Pack Size:	2.5 & 5 Litres
Shelf Life:	24 months
Temp. Limits:	5°C - 32°C

Components

- Advantage® for Metal Primer with Graphene
2.5L & 5L Tins



No responsibility can be taken by the manufacturers where conditions of use are beyond our control. All products should be used in accordance with the manufacturer's instructions. For further information please refer to the application guide and Material Safety Data Sheet. This information and guidance is given in good faith and without prejudice and liability, Technical and Safety Data must be observed. All coverages are given as a guide only, as volumes will vary with profile, porosity and method of application. Loss factors should also be taken into account.

ALLTIMES COATINGS

EXPERIENCE THE DIFFERENCE IN EVERY COAT

Alltimes Coatings, Units C & D,
Station Road Industrial Estate,
South Woodchester, Stroud,
Gloucestershire. GL5 5EQ. UK

T: 01453 872 850

E: info@alltimescoatings.co.uk

W: www.alltimescoatings.co.uk