

AT 2K Graphene Epoxy Primer Activator

A two pack epoxy primer designed for superior corrosion protection to ferrous substrates dries to a semi-gloss finish. Has excellent surface properties allowing for maximum adhesion of a wide variety of topcoat systems. A high solid, high opacity, medium build product, allows for single coat application in most circumstances. Typically applied to shot-blasted steel, skips, fabrications, plant, and machinery.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Product Name:	Alltimes 2K Graphene Epoxy Primer Activator
Product Code:	-

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Identified Users:	PC9a: Coatings and paints, thinners, paint removers
-------------------	---

1.3 Details of the Supplier of the Safety Data Sheet

Supplier:	Alltimes Coatings Limited Unit 17A, Nailsworth Mills Estate, Nailsworth, Gloucestershire, GL6 0BS. UK
-----------	--

1.4 Emergency Contact Numbers

Telephone:	01455 272 278
Mobile:	07773 329 424

SECTION 2: Hazards Identification

2.1 Classification of the Substance or Mixture Classification (EC 1272/2008)

Classification Under CLP:	Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; H312+H332
Most Important Adverse Effects:	Flammable liquid and vapour. Harmful in contact with skin or if inhaled Causes skin irritation. Causes serious eye irritation.

2.2 Label Elements

Pictogram:	
Signal Word:	Warning
Hazard Statements:	H226: Flammable liquid and vapour. H312+H332: Harmful in contact with skin or if inhaled H315: Causes skin irritation. H319: Causes serious eye irritation.
Precautionary Statements:	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241: Use explosion-proof electrical/ventilating/lighting/... equipment. P260: Do not breathe dust/fume/gas/mist/vapours/spray. P280: Wear protective gloves/protective clothing/eye protection/face protection.

2.3 Other Hazards

Other Hazards:	In use, may form flammable / explosive vapour-air mixture.
----------------	--

SECTION 3: Composition/Information on Ingredients

3.1 Mixtures

XYLENE	50-70%
EINECS:	215-535-7
CAS Number:	1330-20-7
Classification:	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315
BUTAN-1-OL	1-10%
EINECS:	200-751-6
CAS Number:	71-36-3
Classification:	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First Aid Measures

4.1 Description of First Aid Measures

Eye Contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.
Skin Contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.
Ingestion:	Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Eye Contact:	There may be irritation and redness. The eyes may water profusely.
Skin Contact:	There may be irritation and redness at the site of contact.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest.
Ingestion:	There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.
Delayed/Immediate Effects:	Immediate effects can be expected after short-term exposure.

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

Immediate / Special Treatment:	Not applicable.
--------------------------------	-----------------

SECTION 5: Firefighting Measures

5.1 Extinguishing Media

Suitable Extinguishing Media:	Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.
Unsuitable Extinguishing Media:	-

5.2 Special Hazards Arising from the Substance or Mixture

Exposure Hazards:	Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.
-------------------	---

5.3 Advice for Firefighters

Advice for Firefighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes
--------------------------	---

SECTION 6: Accidental Release Measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition
-----------------------	--

6.2 Environmental Precautions

Environmental Precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.
----------------------------	---

6.3 Methods & Material for Containment and Cleaning

Methods for Cleaning Up:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks
--------------------------	--

6.4 Reference to Other Sections

Reference to Other Sections:	See section 8.
------------------------------	----------------

SECTION 7: Handling and Storage

7.1 Precautions for Safe Handling

Handling Requirements:	Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.
------------------------	--

7.2 Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions:	Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.
---------------------	--

7.3 Specific End Use(s)

Specific End Use(s):	No data available.
----------------------	--------------------

SECTION 8: Exposure Controls/Personal Protection

8.1 Control Parameters Occupational Exposure Limits

XYLENE	8 hour TWA	15 min. STEL
Workplace Exposure Limits:	220 mg/m ³	441 mg/m ³
Respirable Dust:	-	-

BUTAN-1-OL	8 hour TWA	15 min. STEL
Workplace Exposure Limits:	-	154 mg/m ³
Respirable Dust:	-	-

8.2 Exposure Controls

Appropriate Engineering Controls:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition
Respiratory Protection:	Self-contained breathing apparatus must be available in case of emergency.
Eye/Face Protection:	Safety glasses. Ensure eye bath is to hand.
Hand Protection:	Protective gloves.
Skin/Body Protection:	Protective clothing.

SECTION 9: Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Appearance:	Liquid
Colour:	Yellow-Tan
Odour:	Characteristic
Viscosity:	No data available
Flash Point:	23 - 60°C

SECTION 10: Stability and Reactivity

10.1 Reactivity

Reactivity:	Stable under recommended transport or storage conditions.
--------------------	---

10.2 Chemical Stability

Stability:	Stable under normal conditions. Stable at room temperature.
-------------------	---

10.3 Possibility of Hazardous Reactions

Possibility of Hazardous Reactions:	Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.
--	---

10.4 Conditions to Avoid

Conditions to Avoid:	Heat. Hot surfaces. Sources of ignition. Flames.
-----------------------------	--

10.5 Incompatible Materials

Materials to Avoid:	Strong oxidising agents. Strong acids.
----------------------------	--

10.6 Hazardous Decomposition Products

Hazardous Decomposition Products:	In combustion emits toxic fumes.
--	----------------------------------

SECTION 11: Toxicological Information

11.1 Information on Toxicological Effects Acute Toxicity

XYLENE			
ORL:	Mouse	LD50	2119 mg/kg
ORL:	Rat	LD50	4300 mg/kg
SCU:	Rat	LD50	1700 mg/kg

BUTAN-1-OL			
IVN:	Rat	LD50	310 mg/kg
ORL:	Mouse	LD50	2680 mg/kg
ORL:	Rat	LD50	790 mg/kg

Hazard:	Route:	Basis:
Acute Toxicity (ac. tox. 4):	INH DRM	Hazardous: calculated
Skin Corrosion/Irritation:	DRM	Hazardous: calculated
Serious Eye Damage/Irritation:	OPT	Hazardous: calculated

11.2 Information on Symptoms and Route of Exposure

Eye Contact:	There may be irritation and redness. The eyes may water profusely.
Skin Contact:	There may be irritation and redness at the site of contact.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest.
Ingestion:	There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.
Delayed/Immediate Effects:	Immediate effects can be expected after short-term exposure.

11.3 Toxicological Information on Ingredients

Toxicology:	No data available.
-------------	--------------------

SECTION 12: Ecological Information

12.1 Toxicity

Toxicity:	No data available.
-----------	--------------------

12.2 Ecological Information

Persistence and Degradability:	Biodegradable.
--------------------------------	----------------

12.3 Bioaccumulative Potential

Bioaccumulative Potential:	No bioaccumulation potential.
----------------------------	-------------------------------

12.4 Mobility in Soil

Mobility:	Readily absorbed into soil.
-----------	-----------------------------

12.5 Results of PBT and vPvB Assessment

Results of PBT and vPvB Assessment:	This product does not contain any substances classified as PBT or vPvB.
-------------------------------------	---

12.6 Other Adverse Effects

Other Adverse Effects:	Negligible ecotoxicity.
------------------------	-------------------------

SECTION 13: Disposal Considerations

13.1 Waste Treatment Methods

General Information:	Transfer to a suitable container and arrange for collection by specialised disposal company. Note: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.
----------------------	--

SECTION 14: Transport Information

14.1 UN Number

UN Number:	UN1263
------------	--------

14.2 UN Proper Shipping Name

UN Shipping Name:	PAINT RELATED MATERIAL
-------------------	------------------------

14.3 Transport Hazard Class(es)

Transport Hazard Class(es):	3
-----------------------------	---

14.4 Packaging Group

Packing Group:	I
----------------	---

14.5 Environmental Hazards

Environmental Hazards:	Environmentally hazardous substance? - Yes. Environmentally hazardous marine pollutant? - No.
------------------------	--

14.6 Special Precautions for User

Special Provision:	No special precautions.
--------------------	-------------------------

Tunnel Restriction Code:	2 (D/E)
--------------------------	---------

14.7 Transport in Bulk According to Annex II of MARPOL and the IBC Code

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code:	-
---	---

SECTION 15: Regulatory Information

15.1 Safety, Health and Environmental Regulations / Legislation Specific for the Substance or Mixture

Specific Regulations:	Not applicable.
-----------------------	-----------------

15.2 Safety, Health and Environmental Regulations/Legislation

Chemical Safety Assessment:	A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.
-----------------------------	---

SECTION 16: Other Information

16.1 Other Information

Other Information:	According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Hazard Statements in Full:	H226: Flammable liquid and vapour. H302: Harmful if swallowed. H312: Harmful in contact with skin. H312+H332: Harmful in contact with skin or if inhaled. H315: Causes skin irritation. H318: Causes serious eye damage. H319: Causes serious eye irritation. H332: Harmful if inhaled. H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness.
Legal Disclaimer	The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

ALLTIMES
COATINGS
EXPERIENCE THE DIFFERENCE IN EVERY COAT

Alltimes Coatings Ltd.
Unit 17A, Nailsworth Mills Estate,
Nailsworth, Gloucestershire,
GL6 0BS. UK

T: 01453 872 850
E: info@alltimescoatings.co.uk
W: www.alltimescoatings.co.uk

No responsibility can be taken by the manufacturers where conditions of use are beyond our control. All products should be used in accordance with the manufacturer's instructions. For further information please refer to the application guide and Material Safety Data Sheet. This information and guidance is given in good faith and without prejudice and liability, Technical and Safety Data must be observed. All coverages are given as a guide only, as volumes will vary with profile, porosity and method of application. Loss factors should also be taken into account.